



C3T (Wi-Fi)

Be There for You, Rain or Shine

A Wi-Fi bullet camera offering Full HD 1080p video for protection rain or shine.

Key Features



FHD 1080p



Dual-Stream



Long Range Wi-Fi
Dual External Antennas



Night Vision Up to 100ft/30M



Waterproof Mic Pickup 16ft/5M



Dustproof and Waterproof
IP66



Powerful, dual external antennas

It is equipped with powerful, dual external Wi-Fi antennas, for long-range transmission with strong penetration and anti-interference capabilities.

Security for all seasons

With an IP66-rated weatherproof design, the C3W (ezGuard) is a reliable and durable guard that can protect you in all types of weather: rain, sunshine or even snow.




30m night vision

The integration of efficient infrared lighting, an anti-reflection panel and ICR infrared filter enables excellent night vision up to 30 meters.



Instant alerts (manual activation required) !

The C3W (ezGuard) watches for movement. It will take a picture and send alerts to your smartphone when it detects motions.



360° swivel and base

With a 360° swivel and base, the C3W (ezGuard) is ideal for both ceiling and wall-mounted installations.



Camera

Image Sensor	1/2.7" 2MP Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8mm@ F2.0, view angle:104° (Horizontal), 118°(Diagonal) 4mm@ F2.0, view angle:87° (Horizontal), 102°(Diagonal) 6mm@ F2.0, view angle:54° (Horizontal), 62°(Diagonal)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
DNR	3D DNR
WDR	Digital WDR

Compression

Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	HD; balance; and fluency. Adaptive bit rate.

Image

Max. Resolution	1920 × 1080
Frame Rate	50Hz @ 25fps, 60Hz @ 30fps; adaptive frame rate of network transmission
Image setting	Brightness, contrast, saturation, etc. (Configure via EZVIZ Studio)
BLC	Support

Network

Smart Alarm	Intelligent motion detection
One-key configuration	Smart Config (Wi-Fi One Push Configuration) Sound wave Configuration
Protocol	Ezviz cloud proprietary protocol
Interface Protocol	Ezviz cloud proprietary protocol
General Function	Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Wa-termark

Interface

Wired network	1RJ45 Ethernet Port ,adaptive rate of 10/100Mbps
---------------	--

Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n Draft
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Support 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :150Mbps

General

Operating Conditions	-22°F to 140 °F (-30°C ~ 60°C), Humidity 95% or less (non-condensing)
Power Supply	DC 12V±10%
Power Consumption	MAX. 6W
IP Grade	IP66
IR Range	MAX. 100ft
Dimensions (mm)	0.49ft x 0.23ft x 0.23ft (151mm x 71.6mm x 71.6mm)
Weight	0.780 lb (354g)

Package Contents:

- C3W (ezGuard) X 1
- Power Adapter with 1.5 Meters Power Cable X 1
- Mounting Template X 1
- Screw Kit X 1
- Waterproof Kit X 1
- Quick Start Guide X

Requirements

- Operating Conditions: -30°C ~ 60°C, Humidity 95% or less (non-condensing)

Certificates

FCC/UL/IC/NOM/CE/RoHS/WEEE/REACH

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.
Other brands and product names are trademarks or registered trademarks of their respective holders.

<https://www.ezvizlife.com/>

SICE DISTRIBUTORE UFFICIALE: www.sicetelecom.it