



## Model Parameters

Name	C2C (Mini O Plus)	C2C (Mini O)
Model	CS-CV206-C0-3B2WFR	CS-CV206-C0-1A1WFR

## Camera

Image Sensor	1/2.7"2MP HD progressive scan CMOS	1/4" 1MP HD progressive scan CMOS
Shutter Speed	Self-adaptive shutter	Self-adaptive shutter
Lens	2.8mm@F2.0, Horizontal angle: 115°, Diagonal angle: 135°	2.8mm@F2.5, Horizontal angle: 90°, Diagonal angle: 111°
Lens Mount	M12	M12
Day & Night	IR-cut filter with auto-switching	IR-cut filter with auto-switching
DNR	3D DNR	3D DNR
WDR	Digital WDR	Digital WDR

## Compression

Video Compression	H.264	H.264
H.264 Type	Main profile	Main profile
Video Bit Rate	HD, balanced and smooth bit rate	HD, balanced and smooth bit rate

## Image

Max. Resolution	1920x1080	1280x720
Image setting	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support	Support

## Network

Storage	Support Micro SD card (Max. 256G)	Support Micro SD card (Max. 256G)
Smart Alarm	Motion detection	Motion detection
Wi-Fi Pairing	SmartConfig (Wi-Fi One-Key Configuration)/AP pairing	SmartConfig (Wi-Fi One-Key Configuration)/AP pairing
Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark
Minimum Network Requirements	2M	1M

## Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 150 Mbps	11b: 11 Mbps, 11g: 54 Mbps, 11n: 150 Mbps

## General

Operating Conditions	-10°C ~ 50°C (14°F ~ 122°F), Humidity 95% or less (non-condensing)	-10°C ~ 50°C (14°F ~ 122°F), Humidity 95% or less (non-condensing)
Power Supply	DC 5V±10%	DC 5V±10%
Power Consumption	Max. 3W	Max. 3W
IR Range	Max. 7.5 meters	Max. 7.5 meters
Product Dimensions	128mm x 58mm x 38mm	128mm x 58mm x 38mm
Packaging Dimensions	149mm x 87.5mm x 91.5mm	149mm x 87.5mm x 91.5mm
Weight	120g	120g