



[Homepage](#) > [Products](#) > [Commercial Antennas](#) > [Accessories](#) > **Mounting Kit**

## MOUNTING KIT

**MT-120025**

**MOUNTING KIT FOR FLAT PANEL ANTENNA**



### CONSTRUCTION

INSTALLATION METHOD	To Pole 2 " – 4.5" Diameter
AZIMUTH RANGE: COARSE	±180°
AZIMUTH RANGE: FINE	None
TILT RANGE: COARSE	-14° to +10°
TILT RANGE: FINE	None
AZIMUTH RESOLUTION STEP	None
TILT RESOLUTION STEP	None
WEIGHT	1.8 kg
PAY LOAD	20 kg (max)

### MATERIALS

BRACKETS	Steel, Zinc Plated per MIL-C-81562 TYPE 3 CLASS 1
CLAMPS	Steel, Zinc Plated per MIL-C-81562 TYPE 3 CLASS 1
FASTENERS	Stainless Steel (Pasivated)

[ADD TO COMPARE PAGE](#)

[TO COMPARE PAGE](#)

### ENVIRONMENTAL

TEMPERATURE	-55°C +71°C
VIBRATION	IEC 60721-3-4 4M5 Random
SHOCK MECHANICAL	IEC 60721-3-4 4M5
HUMIDITY	0-100%
ICE LOADING	25 mm Radial
SALT FOG	IEC 68-2-11 Ka, 500h
WIND LOAD (SURVIVAL)	103.6 kg
FRONT THRUST	8.6 kg
SIDE THRUST	

WAIVER!

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.