


Product information

Installation Cable Cat. 6, U/UTP, 4P, 250 MHz, LSZH, B2ca

R852286
305 m



Cat.6, U/UTP, AWG23 cable. 100 Ohm impedance. Data transmission frequencies of up to 450 MHz.

090.6474

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO/IEC 11801-1 Ed 1.0 2017-11 IEC 61156-5 2 nd ed. EN 50173-1 EN 50288-6-1 TIA 568-C.2
Protection class IP	IP 20
Category	Cat. 6
Cable type	installation cable
Category	Cat. 6
Shielding	U/UTP
Jacket material	LSZH
CPR classification	B2ca
Armour	No protection
Cable overall diameter	6.2mm
Cable design	normal
Stranding	4 pairs
Wire type	Wire
Max. test frequency	250 MHz
Product code description	Inst C6-U/UTP-4P-2 B2ca-AWG23-250MHz-gy Inst C6-U/UTP-4P-2 B2ca-AWG23-250MHz-gy

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	305.0 m / 1001 ft
Color Code RAL	7035 Light gray

Climatic Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Operation temperature	-20 °C to +60 °C / -4 °F to +140 °F
Transport / store temperature	-0 °C to +50 °C / +32 °F to +122 °F