

TwistPort™ Adaptor V2 for Rocket AC

ADAPTOR FOR ROCKET™ 5AC-PTP OR PTMP

TwistPort™ Adaptor V2 introduces
wide frequency range of operation: 5180 - 6400 MHz!

The TwistPort™ Adaptor V2 for Rocket 5AC-PTP and PTMP makes the Rocket™ compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket™ 5AC-PTP or PTMP into the TwistPort™ Adaptor V2 is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.4 Kg / 0.9 lbs – single unit 0.5 Kg / 1.1 lbs – single unit incl. package 11.2 Kg / 24.7 lbs – carton (20 units)
Single Unit	Retail Box: 13.5 × 11.5 × 13 cm
20 Units	Carton Box: 28.5 × 28 × 61 cm

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Ubiquiti Networks™	Rocket™ 5AC-PTP, Rocket™ 5AC-PTMP

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

