

ATRS0003 Analog PWR Sensor


The sensor measures the continuous filling level of a tank giving IoT connectivity to industrial sensors already installed on a production site. It provides warnings should thresholds be exceeded, it monitors the humidity rate, and machine consumption, measures a filling level, analyses the presence of gas, monitor changes in temperatures, the humidity rate, pressure, etc.

BENEFITS

- 2 inputs: 0-10V or 4-20mA
- Possibility of triggering measurement via 2 dedicated inputs
- Locally and remotely configurable
- Low power consumption for optimal autonomy
- Develop new preventive maintenance services, alerts services, or analysis services

APPLICATIONS

- Smart City
- Smart Agriculture
- Smart Industry





Dimensions	105 x 50 x 27 mm
Weight	70 g
Operating Temp	-25°C / +70°C
Housing	IP67 (IP68 on request)
Modes	Periodic modes or event-based modes
Battery	Replaceable battery/external power supply

Standards	Directive 2014/53/EU (RED)
Zone	Sigfox: RC1 / LoRaWAN: EU863-870 /
WM-Bus	868

This sensor works with a LoRaWAN Network

Discover our LoRaWAN Gateway at <https://sicetelecom.it/prodotto/iot/lorawan-gateway/>



www.sicetelecom.it
Via Tazio Nuvolari 53, 55061 Carraia (LU)

Phone: +39 0583980787
Email: info@sicetelecom.it

SICE DISTRIBUTORE UFFICIALE: www.sicetelecom.it