


5-Port Gigabit Desktop Switch with 4-Port PoE

MODEL: TL-SG1005P Datasheet



Highlights

- 5 10/100/1000Mbps RJ45 ports
- With four PoE ports, transfers data and power on one single cable
- Working with IEEE 802.3af compliant PDs, expands home and office network
- Supports PoE Power up to 15.4W for each PoE port
- Supports PoE Power up to 56W for all PoE ports
- 802.1p/DSCP QoS enable smooth latency-sensitive traffic
- Plug and play, no configuration and installation required

Overview

TL-SG1005P is a 5 10/100/1000Mbps ports unmanaged switch that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Power Over Ethernet

4 of the 5 Auto-Negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs).

Overload Arrangement

TL-SG1005P has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is $\geq 56W$, a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.


Port Priority Function

Priority (port 1=port 2=port 3>port 4): This function will help protect the system if the system power becomes overloaded. For example, Port 1, 2 and 4 are using 15.4W (maximum power per port is 15.4W), the system power is 46.2W in total. If there is an additional PD inserted to Port 3 with 10W then the system will cut off Port 4 to protect the system, this means Port 1, 2 will use 15.4W, and Port 3 will use 10W, and no power will be supplied to Port 4.

Easy of Use

TL-SG1005P is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the TP-Link TL-SG1005P 5-Port Gigabit Desktop Switch with 4-Port PoE is a great selection for expanding your home or office network.

Specifications

Interface & Performance	
Product Picture	
Model	TL-SG1005P
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3af
Interface	5*10/100/1000Mbps RJ45 Ports with 4 PoE Ports (Port 1 to Port 4) AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Max Power Consumption	3.95 W (220V/50Hz. no PD connected) 64.44 W (220V/50Hz. with 56w PD connected)
Max Heat Dissipation	13.48 BTU/h (no PD connected) 219.87 BTU/h (with 56w PD connected)
PoE Ports (RJ45)	Standard: 802.3 af compliant PoE Ports: Port1- Port4 Power Supply: 56W
Transmission Method	Store-And-Forward
Switching Capacity	10Gbps
Mac Address Table	2K
Fan Quantity	Fanless
External Power Supply	External Power Adapter(Output: 48VDC / 1.25A)
LED	Power, Link/Act, PoE Status, PoE Max
Dimensions (W x D x H)	3.9 x 3.9 x 1.0 in. (99.8 x 98 x 25 mm)
Certification	FCC, CE, RoHS
Package Contents	TL-SG1005P, Power Adapter, User Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90%RH, non-condensing Storage Humidity: 5%~90%RH, non-condensing

www.tp-link.com

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2017 TP-Link Technologies Co., Ltd. All rights reserved.



SICE DISTRIBUTORE UFFICIALE: www.sicetelecom.it