



EX220

Router Dual Band Wi-Fi 6 AX1800

CARATTERISTICHE HARDWARE

Interfaccia	1 10/100/1000 Mbps RJ45 WAN Port, 4 10/100/1000 Mbps RJ45 LAN Ports
Tasto	Power On/Off Button, Reset Button, WPS/Wi-Fi Button
Alimentatore esterno	12V/1A
Dimensioni (L x P x A)	10.2 × 5.3 × 1.6 in (260.2 × 135.0 × 41.6 mm)
Tipo di antenna	Four External antennas
Guadagno antenna	2 x 4dBi for 2.4 GHz and 2 x 5dBi for 5 GHz

CARATTERISTICHE WIRELESS

Standard wireless	IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/g/b 2.4 GHz
Frequenza	2.4 GHz and 5 GHz
Signal rate	1201 Mbps at 5 GHz, 574 Mbps at 2.4 GHz*

CARATTERISTICHE WIRELESS

Funzionalità wireless	Enable/Disable Wireless Radio, WMM, Wireless Statistics
Sicurezza wireless	WPA/WPA2/WPA3 encryptions
Potenza di trasmissione	CE: <20dBm (2.4 GHz), <23dBm (5.17 GHz–5.71 GHz) FCC:<30dBm (2.4 GHz & 5.15 GHz–5.825 GHz)
Schedulazione wireless	Support 2.4 GHz and 5 GHz Wireless Schedule
Mesh Technology	EasyMesh Compatible, and support 802.11k/v/r

CARATTERISTICHE SOFTWARE

Modalità operative	Router, Access Point
Tipo WAN	Dynamic IP/Static IP/PPPoE/PPTP/L2TP(Multi-EWAN)
Gestione	Access Control, Remote Management, TR-069(TR-098/TR-181), TR-111, TR-143
DHCP	Server, DHCP Client List, Address Reservation
Port forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, NO-IP
VPN pass-through	IPSec, PPTP, L2TP
Gestione accessi	Parental Control, White List, Black List

CARATTERISTICHE SOFTWARE

Firewall	DoS, SPI Firewall, IP and MAC Address Binding
Protocolli	IPv4, IPv6
Caratteristiche avanzate	Muti-SSID, TX Beamforming, MU-MIMO, DL/UL OFDMA, Airtime Fairness, Guest Network
VPN Server	PPTP, OpenVPN, IPSec

ALTRO

Contenuto della confezione	AX1800 Wi-Fi 6 Router EX220 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
Requirements	Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Subscription with an internet service provider (for internet access)
Ambiente	Operating Temperature: 0°C–40°C (32°F–104°F) Storage Temperature: -40°C–60°C (-40°F–140°F) Operating Humidity: 10%–90% non-condensing Storage Humidity: 5%–90% non-condensing