

TP-LINK ARCHER NX210 ROUTER GIGABIT 5G WIFI6 DUAL BAND

Network Mode	5G: N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N77/N78 4G: FDD-LTE: B1/B3/B5/B7/B8/B20/B28(2100/1800/850/2600/900/800/700 MHz) TDD-LTE: B38/B40/B41/B42/B43(2600/2300/2500/3500/3700 MHz) 3G: DC-HSPA+/HSPA/UMTS:B1/B5/B8(2100/850/900 MHz)
Speed	5G Download Speed 4.67 Gbps Upload Speed 1.46 Gbps 4G LTE Cat 19: Download Speed 1.6 Gbps Upload Speed 200 Mbps
SIM Type	Nano SIM Card Slot
CARATTERISTICHE HARDWARE	
Interfaccia	2×Gigabit LAN Ports 1×Gigabit LAN/WAN Port 1×Nano SIM Card Slot 2×SMA ports for 5G/4G External Antennas 1×Power port

CARATTERISTICHE HARDWARE

Tasto	Wi-Fi/RESET Button, Power Button, WPS Button
Alimentazione	12V/2A
Dimensioni (L x P x A)	3.9 x 3.9 x 7.5 in (99 x 99x 190 mm)
Antenna	2×Internal Wi-Fi Antennas 8×Internal NR/LTE Antennas

CARATTERISTICHE WIRELESS

Standard wireless	IEEE 802.11a/n/ac/ax 5 GHz IEEE 802.11b/g/n/ax 2.4 GHz
Frequenza	2.4 GHz and 5 GHz
Signal rate	574 Mbps at 2.4 GHz, 1201 Mbps at 5 GHz
Sensibilità di ricezione	5 GHz: 11a 54M: -80 dBm 11ax HE20: -68 dBm 11ax HE40: -65 dBm 11ax HE80: -62 dBm 11ac VHT20: -76 dBm 11ac VHT40: -72 dBm 11ac VHT80: -68 dBm 11n HT20: -79 dBm 11n HT40: -75 dBm 2.4 GHz: 11g 54M: -78 dBm 11ax HE20: -65 dBm 11ax HE40: -62 dBm 11ac VHT20: -73 dBm 11ac VHT40: -68 dBm 11n HT20: -75 dBm 11n HT40: -72 dBm

CARATTERISTICHE WIRELESS

Funzionalità wireless	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
Sicurezza wireless	WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3 encryptions

CARATTERISTICHE SOFTWARE

QoS (Quality of Service)	Bandwidth Control
Modalità operative	3G/4G/5G Router, Wireless Router
Tipo WAN	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Gestione	Access Control, Local Management, Remote Management, reboot schedule
DHCP	Server, DHCP Client List, Address Reservation
Port forwarding	ALG, Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	TP-Link, DynDns, NO-IP
Firewall	DoS, IPv4 SPI Firewall, IPv6 Firewall, IP and MAC Address Binding, Access Control
Protocolli	IPv4, IPv6
Rete ospiti	2.4 GHz guest network x 1, 5 GHz guest network x 1

CARATTERISTICHE SOFTWARE	
VPN Server	PPTP VPN, IPSec VPN, OpenVPN
OTHER	
Network Services Enabled by Default	Web Server Manage and configure device through web (HTTP/HTTPS) • Port: 80/443 Protocol: TCP
	DHCP Server IP address assignment (DHCP) • Port: 67 Protocol: UDP
	IPv6 DHCP Server IP address assignment (DHCPv6) • Port: 547 Protocol: UDP
	DNS DNS • Port: 53 Protocol: TCP
	App management Manage and configure device through app • Port: 22 Protocol: TCP • Port: 20002 Protocol: TCP
ALTRO	
Certificazione	CE, RoHS

ALTRO

Contenuto della confezione	5G AX1800 Wireless Dual Band Gigabit Router Archer NX210 RJ45 Ethernet Cable Power Adapter Quick Installation Guide
Requirements	Edge, Firefox, Chrome, Safari, or other JavaScript-enabled browser *You are recommended to use the latest version
Ambiente	Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing