

UISP Router Pro

UISP-R-Pro



DATASHEET

Mechanical

Dimensions 442.4 x 200 x 43.7 mm (17.4 x 7.9 x 1.7")

Weight 3.3 kg (7.2 lb)

Enclosure materials SGCC steel, polycarbonate/ABS

Hardware

Processor Quad-core ARM® Cortex®-A57 at 1.7 GHz

Memory 4 GB DDR4

Onboard	16 GB eMMC
Networking interface	(8) GbE RJ45 LAN ports (1) GbE RJ45 WAN port (4) 1/10G SFP+ ports
Management interface	Ethernet Bluetooth
Power method	(1) Universal AC input, 100–240V AC, 1.5A Max, 50/60 Hz (1) Power TransPort DC input 27V DC, 2.2A
Power supply	AC/DC, Internal, 60W
Supported voltage range	100–240V AC
Max. power consumption	50W
ESD/EMP protection	Air: ± 15kV, contact: ± 8kV
LCM display	(1) 1.3" touchscreen
Ambient operating temperature	-10 to 50° C (14 to 122° F)

Ambient operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

LEDs

RJ45 data ports Speed/link/activity

SFP+ data ports Speed/link/activity

Software

Management application UISP: Version 1.4.5 and later

NDAA Compliant Yes

